






**ORDERING GUIDE FOR
PRESSURE GAUGES**



Ordering a particular Budenberg Pressure Gauge is an easy process. This guide shows an example of how to specify the exact type of Budenberg Gauge required. Codes for optional features are listed on the back of each product data sheet. Add these codes at the end of the product code when necessary.

SAMPLE

Model Number	766GP	View Models we offer in our PRODUCT RANGE datasheet.				
Dial Size	10	63	63 mm			
		10	100 mm			
		15	150 mm			
		20	200 mm			
		25	250 mm			
Mounting	A					
		A	B	C	D	E
		A	Direct Mount Bottom Entry			
		B	Surface Mount Bottom Entry with Wall / Back Flange			
		C	Direct Mount Rear Entry			
		D	Flush Panel Mount Rear Entry with 3 Hole Front Flange			
		E	Flush Panel Mount Rear Entry with U Bracket			
		Type E is not available on Safety Pattern (GP) Gauges				
Connection Size	4	1	1/8"			
		2	1/4"			
		3	3/8"			
		4	1/2"			
Thread Type	1	1	NPT			
		2	BSP Parallel			
		3	BSP Taper			
Scale Type	P	V	Vacuum			
		P	Pressure			
		C	Compound			
Range	100	100	Maximum Pressure Range			
Units	BAR	KPA	Kilo Pascals			
		PSI	Pounds per Square Inch			
		BAR	Bar			
Options	LF	LF	Liquid Filled			
		O	Other options are available, refer to other product datasheets.			

766GP10A41P100BAR-LF

766GP, 100mm dial size, Direct Mount Bottom Entry, 1/2" NPT, 0/100 Bar, Liquid Filled Case.